

05/05/98
JACOBY, KATZ, U.S. PTO
TELEPHONE
937/298-2811

JACOX, MECKSTROTH & JENKINS

ATTORNEYS AT LAW

PATENT, TRADEMARK & COPYRIGHT MATTERS

2310 FAR HILLS BUILDING

DAYTON OHIO 45419-1575

FACSIMILE
937/298-7418

May 5, 1998

Box PATENT APPLICATION
Assistant Commissioner for Patents
Washington, D.C. 20231

EXPRESS MAIL NO
EI285587695US

Sir:

Enclosed is a patent application identified as follows:

Inventor(s) : Philip G. Morton, David A. Stammen,
Michael T. Chaney & Ricky Hoskins
Title : EXTRUDED PLASTIC WINDOW FRAME WITH
PERIPHERAL CHANNEL FOR RECEIVING EXTERIOR
SIDING
Docket No. : 7663
Specification : 14 pages (including 20 claims) and an
Abstract
Drawing(s) : 3 Sheets
Declarations : Patent Application Declaration
Check : For the filing fee computed as follows:

Basic Fee \$790.00

Additional Fees:

Total number of claims in
excess of 20, times \$22 0.00

Number of independent claims
(5) minus 3, times \$82 164.00

Total Filing Fee \$954.00

Assignee : Dayton Technologies, Inc.
Suggested Class : Class 52, Subclass 204.1

The Commissioner is hereby authorized to charge any additional fees which may be required during pendency of this application and are not otherwise paid for when due, or credit any overpayment, to Account No. 10-0220.

Respectfully submitted,

JACOX, MECKSTROTH & JENKINS

Alan F. Meckstroth
Alan F. Meckstroth
Reg. No. 22,607

AFM:pm
Enclosures

Please type a plus sign (+) inside this box → ☐

PTO/SB/05 (2/98)
Approved for use through 09/30/2000. OMB 0851-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No. 7663

First Inventor or Application Identifier Philip G. Morton

Title EXTRUDED PLASTIC WINDOW FRAME WITH PERIPHERAL CHANNEL FOR RECEIVING EXTERIOR SIDING

Express Mail Label No.

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. ☐ * Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
2. ☒ Specification [Total Pages 14]
(preferred arrangement set forth below)
 - Descriptive title of the invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the invention
 - Brief Summary of the invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 3]
4. Oath or Declaration [Total Pages 2]
 - a. ☒ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 C.F.R. § 1.63(d))
(for continuation/divisional with Box 17 completed)
(Note Box 5 below)
 1. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation By Reference (useable if Box 4b is checked)
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered to be part of the disclosure of the accompanying application and is hereby incorporated by reference therein.

6. ☐ Microfiche Computer Program (Appendix)
7. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☒ Assignment Papers (cover sheet & document(s))
9. ☐ 37 C.F.R. § 3.73(b) Statement (when there is an assignee) ☐ Power of Attorney
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
 - * Small Entity Statement(s) ☐ Statement filed in prior application, Status still proper and desired (PTO/SB/09-12)
14. ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)
15. ☐ Other:
16. ☐ Other:

* NOTE FOR ITEMS 1 & 14: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).

17. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: _____

Prior application information: Examiner _____ Group / Art Unit: _____

18. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label (Insert Customer No. or Attach bar code label here) or ☒ Correspondence address below

Name	Alan F. Meckstroth, Esq.				
Address	Jacox, Meckstroth & Jenkins 2310 Far Hills Bldg.				
City	Dayton	State	Ohio	Zip Code	45419-1575
Country	USA	Telephone	937 298-2811	Fax	937 298-7418

Name (Print/Type)	Alan F. Meckstroth	Registration No. (Attorney/Agent)	22607
Signature	<i>A Meckstroth</i>	Date	5-5-98

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

EXTRUDED PLASTIC WINDOW FRAME WITH PERIPHERAL CHANNEL
FOR RECEIVING EXTERIOR SIDING

Background Of The Invention

The present invention relates to hollow or tubular window frames of extruded plastics material and of the general type disclosed in U.S. Patents No. 4,941,288 and No. 5,003,747 which issued to the Assignee of the present invention. In such a window frame, a pair of vertical jamb
5 members are rigidly connected by a horizontal sill member and a horizontal head member, and each of the tubular members are formed by extruding a rigid plastics material such as polyvinylchloride (PVC). Preferably, the window frame is formed by mitering the opposite ends of the extruded linear frame members and then welding the mating mitered
10 corners together to provide substantial rigidity.

The PVC frame may support a fixed picture window unit or one or more operable or movable window units, as shown in the above-mentioned patents. The frame is installed within a rough opening of a building wall, and sometimes the wall has an exterior surface covered by
15 aluminum or PVC siding, usually in the form of lapped siding. After a window frame is positioned within the rough opening of a building wall, it is secured by nails or screws extending through a laterally outwardly projecting nailing flange extruded as an integral part of each frame member. When exterior siding is to be installed, it is
20 common to install a separate J-channel around the exterior projecting portion of the window frame. The J-channel has a nailing flange portion which is attached to the building wall, a portion which covers the ends of the siding panels and a returned flange portion which overlies the end portions or edge portions of the siding panels.

25 A typical J-channel is disclosed in U.S. Patent No. 4,608,800 and allows for longitudinal expansion and contraction of each siding panel while covering the expansion gap between the ends of the siding and the window frame. In factory manufactured housing units, it is known to construct a window frame with relatively flat extruded linear frame
30 members and with an integrally extruded J-channel formed in part by the

050505 050505 050505

5 window frame nailing flange, for example, as disclosed in U.S. Patent No. 5,660,010. A similar window frame construction is disclosed in U.S. Patent No. 2,983,001. While the frame constructions disclosed in these patents may be acceptable for manufactured housing units, the frame structure would not be acceptable in site constructed homes where the window frame units must provide substantial strength, rigidity and an attractive appearance. It is also sometimes desirable for a window frame to provide for conveniently installing wood sill, head and jamb extenders within the interior of the building in order to provide a wood interior window frame for the window assembly or unit.

Summary Of The Invention

15 The present invention is directed to an improved frame for a window assembly and which is ideally suited for installation in a rough opening within a building wall which is to be covered by exterior siding panels. The window frame of the invention includes tubular sill, head and jamb members of extruded plastics material, and the frame members are joined together by mitered welded corners to form a rigid window frame for either an operable window unit or a fixed picture window unit. Each of the extruded sill, head and jamb members of the frame includes laterally spaced inner and outer walls integrally connected by laterally extending transverse walls, and each of the frame members has a rigid outwardly projecting exterior portion which define a peripheral cavity or channel for receiving the end or edge portions of exterior siding mounted on the building wall. The exterior projecting portions of the sill, head and jamb members also provide a neat and attractive appearance for the window assembly, and the exterior projecting portions do not interfere with access to the nailing flange for securing the window unit within the wall opening.

30 In accordance with preferred embodiments of the invention, the exterior projecting portions of the sill, head and jamb members forming the window frame, have laterally spaced walls which form a rigid and durable extension of the sill member and also form a rigid and decorative trim appearance for the head and jamb members. The recessed

channel within each of the frame members is also formed by a double wall exterior flange which projects laterally outwardly in parallel spaced relation to an exterior transverse wall of the frame member. The interior transverse wall of each of the tubular sill, head and jamb members may also be formed with a longitudinally extending recess or cavity for receiving the edge portions of interior sill, head and jamb extenders in order to simplify the installation of interior wood extenders and provide the window assembly with a clean and neat interior appearance.

Other features and advantages of the invention will be apparent from the following description, the accompanying drawings and the appended claims.

Brief Description Of The Drawings

FIG. 1 is a fragmentary section of an installed operable window unit or assembly and showing a sill member constructed in accordance with the invention;

FIG. 2 is a fragmentary section similar to FIG. 1 and showing a jamb member for the operable window assembly;

FIG. 3 is a fragmentary section of an installed picture window assembly and showing a sill member constructed in accordance with the invention;

FIG. 4 is a fragmentary section similar to FIG. 3 and showing a jamb member for the picture window assembly; and

FIG. 5 is a fragmentary section of a sill member of an operable window assembly constructed in accordance with a modification of the invention.

Description Of The Preferred Embodiments

Referring to FIG. 1, an operable window assembly or unit 10 is shown installed in a rectangular rough opening 12 of a building wall 14 with the rough opening defined at the bottom by wood frame members 16. In a typical construction, the interior of the wall is formed by dry wall sheets 18, and the exterior surface of the wall is formed by

exterior sheeting 22 also secured to the wall framing. The window unit 10 includes an elongated linear sill member 25 which is formed as a hollow or tubular extrusion, preferably of a rigid plastics material such as polyvinylchloride (PVC).

5 The sill member 25 includes a slightly inclined inner wall 27 which converges slightly with a generally parallel and laterally spaced outer wall 29. The walls 27 and 29 are integrally connected by laterally extending transverse walls 31, 32 and 33 to provide the sill member 25 with a hollow box-like rigid construction. The outer wall 29
10 of the sill member 25 rests upon a spacer or shim strip or pads 36 which are placed within the rough opening 12, and a nailing flange 38 projects laterally outwardly or downwardly for securing the sill member 25 of the window frame to the wall 14 by means of longitudinally spaced screws or nails 41.

15 The sill member 25 also includes an integrally extruded exterior portion 45 which is formed by laterally spaced double walls 46 and 48 which project outwardly from the exterior transverse wall 31 and support an integrally extruded box-like flange 50 having parallel spaced walls 52 and defining an accessory groove 54. The double wall
20 flange 50 cooperates with the opposing transverse wall 31 and the projecting double walls 46 and 48 to define a longitudinally extending recess or channel 58 located laterally inwardly of the outer wall 29 of the sill member 25.

The operable window unit 10 shown in FIG. 1 is also illustrated
25 with an extruded PVC sash member 61 which forms the bottom of a sash frame 62 having welded mitered corners and enclosing a glass unit 63 with dual glass panes 64 spaced by a metal spacer frame 66 and sealed together by a resilient rubber-like bonding material 68. The bottom sash member 61 has an interior projecting lift rail or handle 72 with
30 a downwardly projecting flange 73, and the glass unit 63 is releasably retained within the sash frame 62 by a set of extruded plastic glazing members 74. A strip 77 of a resilient foam material is bonded to the bottom of the sash member 61 for engaging the top surface of the inner sill wall 27, and a double wall flange 79 is extruded as an integral

part of the sill member 25 and projects upwardly from the inner wall 27 to support a flexible sealing strip 83 which contacts the bottom sash member 61. Preferably, the sill member 25 is also extruded with a pair of ribs 86 which project upwardly from the inner wall 27 and define a channel for receiving a frame 88 of a screen unit 90.

An accessory groove 93 (FIG. 1) is extruded within sill member 25 at the juncture of the outer wall 29 and the interior transverse wall 33, and an extruded plastic interior casing or trim member 95 has an intermediate leg portion 98 which projects into the groove 93 to form a snap-fit connection for retaining the trim member 95 against the sill member 25 and the adjacent dry wall sheet 18. As also shown in FIG. 1, the channel 58 within the sill member 25 receives the upper edge portion of exterior siding 100 which is illustrated in the form of extruded PVC lap siding. The exterior flange 50 of the sill member 25 covers or conceals the upper edge portion of the siding 100, and the channel 58 allows for vertical expansion and contraction of the siding.

Referring to FIG. 2, the frame of the window assembly or unit 10 includes a pair of vertical jamb members 110 and a head member (not shown) which has the same cross-sectional configuration as the jamb members 110. Since each jamb member 110 has an outer structure which is common with the sill member 25, the same reference numbers have been used for the same corresponding walls and components and also for the interior molding or trim member 95. Each jamb member 110 also includes a set of integrally extruded C-shaped channel portions 114 and 116 which provide guide rails or tracks for the lower vertically movable sash frame 62 and a similarly constructed upper sash frame (not shown). The channel portions 114 and 116 of each jamb member 110 also enclose conventional spring bias counterbalancing mechanisms (not shown) for each movable sash frame and the enclosed glass unit 63.

Each of the extruded head and jamb members 110 also include a U-shaped channel portion 122 which is connected to the inner wall 27 by a laterally extending wall 124 in plane with the exterior transverse wall 31. The channel portion 122 within each jamb member 110 is partially closed by a frangible rib or flange 127 for laterally

Locating the frame 88 of the screen unit 90. The flange 127 is broken off within the head member (not shown) so that the channel portion 122 may receive the top frame member of the screen unit 90 for retaining the screen unit. The channel portion 122 of each head and jamb member 110 is also integrally connected to the corresponding double wall flange 50 of the exterior portion 45 by an exterior trim wall 132. The wall 132 cooperates with the walls 46 and 124 to form a rigid tubular exterior portion 135 for the jamb and head members. By replacing the wall 48 of the sill member 25 with the laterally spaced trim wall 132 of each jamb member 110, the channel 58 within each jamb member is somewhat deeper in order to provide for greater longitudinal expansion of the vinyl siding 100 having end portions projecting into the channel 58 within each jamb member 110. As also shown in FIG. 2, the rectangular window frame formed by the sill, head and jamb members with welded mitered corners, is positioned laterally or horizontally within the rough opening 12 by a set of screws 137 which connect the outer walls 29 of the jamb members to the adjacent wood frame members 16.

FIGS. 3 and 4 show a sill and jamb construction in accordance with the invention of a rectangular frame for a fixed picture window assembly or unit 150. The frame includes an extruded rigid PVC sill member 152 (FIG. 3) and a pair of jamb members 154 (FIG. 4). The head member of the frame has the same cross-sectional profile as each of the jamb members 154, and each of the sill, head and jamb members of the window unit 150 have walls and components corresponding to those of the frame members 25 and 110 of the operable window unit 10 described above in connection with FIGS. 1 and 2. Accordingly, the common walls and components are identified with the same reference numbers.

In reference to FIG. 3, the extruded sill member 152 also includes an integrally extruded and laterally inwardly projecting box-shaped portion 156 which forms a support for the glazing or glass unit 63. The glass unit 63 is confined between an integrally extruded double wall flange 158 and a removable extruded glazing bead 74. Each of the jamb members 154 includes an integrally extruded L-shaped wall 162 (FIG. 4) which connects the inner wall 27 to integrally extruded

[illegible]

5 The contour of the exterior wall 168 and the walls 156 and 158 provide for matching the appearance of the fixed window unit 150 with the appearance of an adjacent operable or double hung window unit 10 and also provide for locating horizontal mullions or grid members for the glass unit 63 of the fixed window assembly 150 on the same level as
10 the horizontal mullions or grid members within the operable or double hung window assembly 10. The wall 168 also reinforces the projecting wall 46 and thereby adds substantial rigidity to the exterior portion 135 and flange 50 which define the channel 58.

Referring to FIG. 5, an operable window assembly or unit 180 includes an elongated extruded PVC sill member 185 which is constructed substantially the same as the sill member 25 (FIG. 1) except that the sill member 185 is substantially narrower in width than the sill member 25. Accordingly, the components and walls of the window unit 10 shown in FIG. 5 are identified with the same reference numbers as used above to identify the corresponding components and walls except with the addition of a prime mark on each reference number.

In the embodiment shown in FIG. 5, the interior transverse wall 33' defines a longitudinally extending recess or cavity 188 for receiving the edge portion of a wood sill extender 190. The cavity 188 conceals the inner edge portion of the extender 190 and provides for quick and convenient installation as well as a neat appearance for the joint between the sill member 185 and the wood sill extender 190. It is understood that the head and jamb members for the window unit 180 shown in FIG. 5 are also extruded with a narrow width profile and have corresponding cavities for receiving similar wood jamb and head extenders similar to the wood sill extender 190.

From the drawings of the above description, it is apparent that a window unit including a frame constructed in accordance with the present invention, provides desirable features and advantages. For

example, the cross-sectional configuration of the sill members 25 and 152 and the jamb members 110 and 154 provide for producing a rigid rectangular frame since the inner walls 27 and the outer walls 29 and the transverse walls 31-33 all have a common profile and may be welded together at mitered corners. In addition, all of the sill, head and jamb members have common double wall flanges 50 and projecting walls 46 which are welded at the corners, and the additional wall 48 and 48' on the sill members 25, 152 and 185 provide additional strength for the exterior sill portion 45 and 45' of the sill member. As another feature, the exterior trim walls 132 and 168 provide reinforcement and additional strength and rigidity to the projecting exterior portions of the jamb and head members and provide the appearance of a brick molding.

The peripheral recessed cavity or channel 58 within the frame members further provides full access to the nailing flanges 38 around the window frame for securing the frame to the building wall 14 while the channel 58 also provides for receiving and concealing the edge portions of the exterior siding 100 around the frame. Additional features are provided by the width of the frame between the nailing flanges 38 and the plane of the interior transverse walls 33 being the same as the width of the wall 14, and the interior groove 93 adjacent the outer wall 29 of each frame member for receiving the leg portion 98 of the corresponding interior casing or trim member 95. A further feature is provided by the recess cavity 188 (FIG. 5) formed within the interior transverse wall 33' of the sill member 185 and in each jamb and head member for receiving the edge portions of corresponding wood frame extenders such as the sill extender 190. This feature simplifies the installation of the wood frame extenders when desired for the interior of the window opening.

While the forms of window frame herein described constitute preferred embodiments of the invention, it is to be understood that the invention is not limited to these precise forms, and that changes may be made therein without departing from the scope and spirit of the invention as defined in the appended claims.

What is claimed is:

1. A frame for a window assembly adapted to be installed in an opening within a building wall, said frame comprising an elongated tubular sill member connecting a pair of elongated tubular jamb members, each of said sill and jamb members including spaced inner and outer walls connected by longitudinally extending transverse walls, each of said sill and jamb members including an exterior portion projecting outwardly from said inner wall and cooperating with an adjacent said transverse wall to define a channel disposed outwardly from the building wall, and said channels extend laterally inwardly of said outer walls of said sill and jamb members and cooperate for receiving edge portions of exterior siding mounted on the building wall.

2. A frame as defined in claim 1 wherein said exterior portion of said sill member includes laterally spaced walls projecting generally perpendicular outwardly from said adjacent transverse wall to form a continuation of said inner wall of said sill member, and a flange wall projecting laterally outwardly from said laterally spaced walls and cooperating with said adjacent transverse wall to define said channel.

3. A frame as defined in claim 1 wherein said exterior portion of each said jamb member comprises a first wall projecting outwardly from said adjacent transverse wall, an exterior trim wall projecting laterally inwardly from said first wall for reinforcing said first wall, a flange wall projecting laterally outwardly from said first wall and said trim wall and cooperating with said adjacent transverse wall to define said channel, and said trim wall having a lower end mating with said inner wall of said sill member.

4. A frame as defined in claim 1 wherein each of said sill and jamb members includes an accessory groove disposed adjacent the corresponding said outer wall and an interior said transverse wall, and an extruded interior trim strip including an intermediate leg portion projecting into each said groove of said sill and jamb members.

5. A frame as defined in claim 1 wherein each of said jamb members includes integrally extruded guide walls projecting laterally inwardly from the corresponding said inner wall and defining guideways for a movable glass sash frame, and said exterior portion of each said jamb member includes an exterior trim wall having a lower end mating with said inner wall of said sill member.

6. A frame as defined in claim 1 wherein each of said sill and jamb members includes integrally extruded mating walls projecting laterally inwardly from the corresponding said inner wall and defining a recess for receiving a glass picture window unit, and said exterior portion of each said jamb member includes an exterior trim wall having a lower end mating with said inner wall of said sill member.

7. A frame as defined in claim 1 wherein said inner and outer walls of each of said sill and jamb members converge slightly towards the corresponding said channel, and each said exterior portion including a double wall flange cooperating with said adjacent transverse wall to define said channel.

8. A frame as defined in claim 1 wherein an interior said transverse wall of said sill member defines a longitudinally extending cavity between the corresponding said inner and outer walls and adapted for receiving an edge portion of a wood sill extender.

9. A frame for a window assembly adapted to be installed in an opening within a building wall, said frame comprising an elongated tubular sill member and a pair of elongated tubular jamb members, said sill and jamb members being connected by welded mitered corner portions, each of said sill and jamb members including spaced inner and outer walls connected by longitudinally extending transverse walls, a nailing flange projecting laterally outwardly from said outer wall of at least each of said jamb members for securing said frame to the wall within the wall opening, each of said sill and jamb members including

05073029 050599

10 an exterior portion projecting outwardly from a plane defined by said
nailing flanges and cooperating with an adjacent said transverse wall
to define a channel disposed outwardly from the building wall, and said
channels extend laterally inwardly of said outer walls of said sill and
jamb members and cooperate for receiving edge portions of exterior
15 siding mounted on the building wall.

10. A frame as defined in claim 9 wherein said exterior portion of
said sill member includes laterally spaced walls projecting generally
perpendicular outwardly from said adjacent transverse wall to form a
continuation of said inner wall of said sill member, and a double wall
5 flange projecting laterally outwardly from said laterally spaced walls
and cooperating with said adjacent transverse wall to define said
channel.

11. A frame as defined in claim 9 wherein said exterior portion of
each said jamb member comprises a first wall projecting outwardly from
said adjacent transverse wall, an exterior trim wall projecting
laterally inwardly from said first wall for reinforcing said first
5 wall, and a double wall flange projecting laterally outwardly from said
first wall and said trim wall and cooperating with said adjacent
transverse wall to define said channel.

12. A frame as defined in claim 9 wherein each of said sill and jamb
members includes an accessory groove disposed adjacent the
corresponding said outer wall and an interior said transverse wall, and
an extruded interior trim strip including an intermediate leg portion
5 projecting into each said groove of said sill and jamb members.

13 A frame as defined in claim 9 wherein each of said jamb members
includes integrally extruded guide walls projecting laterally inwardly
from the corresponding said inner wall and defining a guideway for a
movable glass sash frame, and said exterior portion of each said jamb

00073020-00000000

18. A frame for a window assembly adapted to be installed in an opening within a building wall, said frame comprising an elongated tubular sill member connecting a pair of elongated tubular jamb members, each of said sill and jamb members including spaced inner and outer walls connected by longitudinally extending transverse walls, each of said sill and jamb members including an exterior portion projecting outwardly from the building wall, each of said jamb members including integrally extruded guide walls projecting laterally inwardly from the corresponding said inner wall and defining guideways for a movable glass sash frame, said exterior portion of each said jamb member including an exterior trim wall having a lower end mating with said inner wall of said sill member, each of said jamb members including integrally extruded walls defining a groove adapted to receive the frame of a screen unit, and a frangible rigid flange projecting into said groove for positioning the screen unit laterally between said jamb members.

19. A frame for a window assembly to be installed in an opening within a building wall having a predetermined width, said frame comprising an elongated tubular sill member and a pair of elongated tubular jamb members, each of said sill and jamb members being an extrusion of rigid plastics material and including spaced inner and outer walls connected by longitudinally extending transverse walls, a nailing flange projecting laterally outwardly from said outer wall of at least each of said jamb members for securing said frame to the wall within the wall opening, each of said sill and jamb members including an exterior portion projecting outwardly from a plane defined by said nailing flanges, and the spacing between said nailing flanges and a plane defined by the interior said transverse walls being substantially the same as said width of said building wall.

20. A frame as defined in claim 19 wherein each of said sill and jamb members includes an accessory groove disposed adjacent the corresponding said outer wall and said interior transverse wall, and an extruded interior trim strip including an intermediate leg portion projecting into each said groove of said sill and jamb members.

Abstract of the Disclosure

A window frame includes tubular sill, head and jamb members of extruded plastics material, and each member has laterally spaced inner and outer walls integrally connected by laterally extending transverse walls. A nailing flange projects laterally outwardly from each outer wall for securing the frame within a wall opening, and each frame member has an integral exterior portion projecting outwardly from the corresponding nailing flanges. The exterior portion of each frame member cooperates with an exterior transverse wall to define a groove or channel extending laterally inwardly from the outer wall for receiving the edge portion of exterior siding. Narrower frame members also have cavities within the interior transverse walls for receiving the edge portions of interior wood sill, head and jamb extenders.

FIG-1




FIG-2




FIG-3




FIG-4





FIG-5



DECLARATION FOR PATENT APPLICATION

Docket No. 7663

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name. I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled EXTRUDED PLASTIC WINDOW FRAME WITH PERIPHERAL CHANNEL FOR RECEIVING EXTERIOR SIDING, the specification of which (check one)

☒ (X) is attached hereto.

☐ () was filed on _____ as Application Serial No. _____ and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, Section 1.56(a). I hereby claim foreign priority benefits under Title 35, United States Code, Section 119 of the foreign application for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Priority Claimed

☐ () Yes ☐ () No

(Number) (Country) (Day/Month/Year Filed)

I hereby claim the benefit under Title 35, United States Code, Section 120 of the United States application below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, Section 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Ser.No.) (Filing Date) (Status-Patented, Pending, Abandoned)

I hereby appoint the following attorneys with full power of appointment, substitution, association and revocation, to prosecute this application and transact all business in the Patent and Trademark Office connected therewith: Alan F. Meckstroth Reg. No. 22,607, and
Matthew R. Jenkins Reg. No. 34,844

Address all telephone calls to (937) 298-2811

Address all correspondence to: JACOX, MECKSTROTH & JENKINS, 2310 Far Hills Building, Dayton, Ohio 45419-1575

DECLARATION FOR PATENT APPLICATION

Docket No. 7663

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor Philip G. MortonInventor's signature *Philip G. Morton* Citizenship USAResidence 7187 Preble County Line Rd., Germantown, Ohio 45327 Date 4 May 98Post Office Address 351 North Garver Rd., Monroe, Ohio 45050-1292Full name of second joint inventor, if any David A. StammenInventor's signature *David A. Stammen* Citizenship USAResidence 492 Moorewood Circle, Dayton, Ohio 45415 Date 5-4-98Post Office Address 351 North Garver Rd., Monroe, Ohio 45050-1292Full name of third joint inventor, if any Michael T. ChaneyInventor's signature *Michael T. Chaney* Citizenship USAResidence 2009 Erie Avenue Middletown, Ohio 45042 Date 5-4-98Post Office Address 351 North Garver Rd., Monroe, Ohio 45050-1292Full name of fourth joint inventor, if any Ricky HoskinsInventor's signature *Ricky Hoskins* Citizenship USAResidence 211 Holly Drive, Franklin, Ohio 45005 Date 5-4-98Post Office Address 351 North Garver Rd., Monroe, Ohio 45050-1292

09073029 45050